

foggia

Commercial

COMMERCIAL STACK TUMBLE DRYER



Fast dry (20-30 minutes), increase productivity & energy cost.



Reversing cylinder, improve large items drying time



LP Gas/ Electric heat



Industrial quality parts
Emerson gas valve, SKF bearing



SPECIFICATION

	FTTG160	FTTG220	FTTG270
Cylinder volume - l / pocket	285	380	477
Capacity - kg / pocket			
1 : 19 ratio	15	20	25
1 : 20 ratio	14	19	24
Cylinder Diameter - mm	745	855	855
Cylinder Depth - mm	655	660	830
Voltage	220/50/1	220/50/1	220/50/1
Motor power (kw) / pocket	0.25	0.55	0.55
Fan (kw) / pocket	0.37	0.37	0.37
Heating Option			
Gas heat - LPG/NLG (BTU)	75000	95000	115000
Electric heat (kw)	10.5	14.4	19.8
Pipe connection			
Gas inlet - inch / pocket	0.5	0.5	0.5
Exhaust - mm / pocket	200	200	200
Air flow (cfm) / pocket	471	589	589
Unit dimension - L x W x H mm	800 x 1161 x 2005	910 x 1208 x 2225	910 x 1378 x 2225
Packing dimension - L x W x H mm	920 x 1281 x 2155	1030 x 1328 x 2375	1030 x 1498 x 2375
Net weight - kg	317	380	395
Gross weight - kg	357	420	435

PT. Anugrah Utama Servisindo

Ruko Bolsena, Blok B33

Gading Serpong - Tangerang Selatan

Ph : +62 8111 799 278